


Description:

The Connor-Winfield's D75A is a 5x7mm Surface Mount Temperature Compensated Crystal Controlled Oscillator (TCXO) with a Tri-State LVCMOS output. Through the use of Analog Temperature Compensation, the D75A is capable of holding sub 1-ppm stabilities over the 0 to 70°C temperature range. The D75A meets STRATUM 3 requirements.



Features:

- 3.3 Vdc Operation
- LVCMOS Output
- Frequency Stability: ± 0.28 ppm
- Temperature Range: 0 to 70°C
- Low Jitter <1ps RMS
- Tri-State Enable/Disable Function
- 5x7mm Surface Mount Package
- Tape and Reel Packaging
- RoHS Compliant / Pb Free

Applications:

- IEEE 1588 Applications
- Synchronous Ethernet slave clocks, ITU-T G.8262 EEC options 1 & 2
- Compliant to Stratum 3, GR-1244-CORE & GR-253-CORE
- Wireless Communications
- Small Cells
- Test and Measurement

Absolute Maximum Ratings

Parameter	Minimum	Nominal	Maximum	Units	Notes
Storage Temperature	-55	-	85	°C	
Supply Voltage (Vcc)	-0.5	-	6.0	Vdc	
Input Voltage	-0.5	-	Vcc+0.5	Vdc	

Operating Specifications

Parameter	Minimum	Nominal	Maximum	Units	Notes
Nominal Frequency (Fo)	-	10.0, 12.8, 19.2, or 20.0	-	MHz	
Frequency Calibration @ 25 °C	-1.0	-	1.0	ppm	1
Frequency Stability vs. Temperature	-0.28	-	0.28	ppm	2
Holdover Stability (Over 24 Hours)	-0.32	-	0.32	ppm	3
Frequency vs. Load Stability	-0.20	-	0.20	ppm	$\pm 5\%$
Frequency vs. Voltage Stability	-0.20	-	0.20	ppm	$\pm 5\%$
Static Temperature Hysteresis	-	-	0.4	ppm	Absolute, 4
Total Frequency Tolerance:	-4.6	-	4.6	ppm	5
Operating Temperature Range:	0	-	70	°C	
Supply Voltage (Vcc)	3.135	3.3	3.465	Vdc	$\pm 5\%$
Supply Current (Icc)	-	-	6	mA	
Period Jitter	-	3	5	ps rms	
Integrated Phase Jitter	-	0.5	1.0	ps rms	6
SSB Phase Noise (Fo = 10 MHz)					
@10Hz offset	-	-80	-	dBc/Hz	
@ 100Hz offset	-	-110	-	dBc/Hz	
@ 1KHz offset	-	-135	-	dBc/Hz	
@ 10KHz offset	-	-150	-	dBc/Hz	
@ 100KHz offset	-	-150	-	dBc/Hz	
Start-up Time	-	-	10	ms	

Enable / Disable Input Characteristics (Pad 8)

Parameter	Minimum	Nominal	Maximum	Units	Notes
Enable Voltage (High)	70%Vcc	-	-	Vdc	7
Disable Voltage (Low)	-	-	30%Vcc	Vdc	7

LVCMOS Output Characteristics

Parameter	Minimum	Nominal	Maximum	Units	Notes
Load	-	15	-	pF	8
Voltage (High) (Voh)	90%Vcc	-	-	Vdc	
(Low) (Vol)	-	-	10%Vcc	Vdc	
Duty Cycle at 50% of Vcc	45	50	55	%	
Rise / Fall Time 10% to 90%	-	-	8	ns	

Package Characteristics

Package: Hermetically sealed crystal mounted on a ceramic package


Environmental Characteristics

Vibration: Vibration per Mil Std 883E Method 2007.3 Test Condition A
 Shock: Mechanical Shock per Mil Std 883E Method 2002.4 Test Condition B.
 Soldering Process: RoHS compliant lead free. See soldering profile on page 2.


Ordering Information

D75A-010.0M, D75A-012.8M, D75A-019.2M or D75A-020.0M

Package Layout



Suggested Pad Layout




* Do not route any traces in the keep out area. It is recommended the next layer under the keep out area is to be ground plane.

Pad Connections


- 1: Do Not Connect
- 2: Do Not Connect
- 3: Do Not Connect
- 4: Ground
- 5: Output
- 6: Do Not Connect
- 7: Do Not Connect
- 8: Tri-State Enable / Disable
- 9: Supply Voltage Vcc
- 10: N/C

Design Recommendations



Attention: To achieve optimal frequency stability, and in some cases to meet the specification stated on this data sheet, it is required that the circuit connected to this TCXO output must have the equivalent input capacitance that is specified by the nominal load capacitance. Deviations from the nominal load capacitance will have a graduated effect on the stability of approximately 20 ppb per pF load difference.

Output Waveform



Test Circuit

